

	Type	L #	Hits	Search Text
1	BRS	L1	5641	(measur\$6 detect\$6 sens\$6 transducer) near3 (fuel) near3 (injection)
2	BRS	L2	1991	1 and (measur\$6 detect\$6 sens\$6 transducer) near3 (temperature)
3	BRS	L3	1144	2 and (measur\$6 detect\$6 sens\$6 transducer) near3 (pressure)
4	BRS	L4	759	3 and (chamber)
5	BRS	L5	634	4 and (ECU CPU controller microprocessor processor computer)
6	BRS	L6	45	5 and (drain\$5)
7	BRS	L7	43	6 and (valve)
8	BRS	L8	25	7 and (piston)
9	BRS	L9	9	8 and (displacement)

	DBs	Time Stamp	Comments	Error Definition	Errors
1	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/23 10:23			0
2	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/23 10:23			0
3	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/23 10:24			0
4	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/23 10:24			0
5	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/23 10:25			0
6	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/23 10:25			0
7	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/23 10:26			0
8	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/23 10:26			0
9	USPAT; US-PGPUB; EPO; JPO; DERWENT	2004/02/23 10:26			0